



**SAFETY DATA SHEET**  
CHEMSET ES 8106 EPOXY ENAMELLING RESIN

Page: 1

Compilation date: 10/10/2017

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** CHEMSET ES 8106 EPOXY ENAMELLING RESIN

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**Company name:** R F Bright Enterprises Ltd  
Unit 6, Access 4.20  
New Hythe Business Park, Bellingham Way  
Aylesford  
Kent  
ME20 7HP  
United Kingdom  
**Tel:** 01622717141  
**Fax:** 01622717163  
**Email:** [enquiries@rfbright.co.uk](mailto:enquiries@rfbright.co.uk)

**1.4. Emergency telephone number**

**Emergency tel:** 08450563563

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark  
GHS09: Environmental



**Signal words:** Warning

[cont...]

# SAFETY DATA SHEET

CHEMSET ES 8106 EPOXY ENAMELLING RESIN

Page: 2

**Precautionary statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P264: Wash hands thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/soap and water.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see instructions on this label).

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	70-90%

1,6 HEXANDIOLDIGLYCIDYLETHER

-	16096-31-4	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317	10-30%
---	------------	---	---	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

[cont...]

# SAFETY DATA SHEET

CHEMSET ES 8106 EPOXY ENAMELLING RESIN

Page: 3

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

[cont...]

# SAFETY DATA SHEET

CHEMSET ES 8106 EPOXY ENAMELLING RESIN

Page: 4

## 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Barely perceptible odour

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

### 10.5. Incompatible materials

**Materials to avoid:** Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

[cont...]

# SAFETY DATA SHEET

CHEMSET ES 8106 EPOXY ENAMELLING RESIN

Page: 5

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms.

[cont...]

**SAFETY DATA SHEET**  
CHEMSET ES 8106 EPOXY ENAMELLING RESIN

Page: 6

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN3082

**14.2. UN proper shipping name**

**Shipping name:** Environmentally Hazardous Substance, liquid, n.o.s.  
(Epoxy Resin (number average molecular weight <700); Hexandioldiglycidylether)

**14.3. Transport hazard class(es)**

**Transport class:** 9

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** Yes

**Marine pollutant:** No

**14.6. Special precautions for user**

**Special precautions:** No special precautions.

**Tunnel code:** E

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

[cont...]

## **SAFETY DATA SHEET**

CHEMSET ES 8106 EPOXY ENAMELLING RESIN

**Page: 7**

**Phrases used in s.2 and s.3:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.